

PU-E210

General Description

PU-E210 is a new EPON ONU product of Picotel company in passive optical network terminal series. It provides 1GE interface, 1 optical fiber access port, and it is very impact. Suitable for home and small business users, can meet the FTTH high-speed data transmission of the application.

Outline



Key Features

- ☑ It takes the PTMP (point to multipoint) network topology, effectively collects and converges scattered Ethernet services, and provides the 10/100/1000M Ethernet standard RJ45 interface, smoothly interconnects with existing networks.
- ☑ The Dynamic Bandwidth Allocation (DBA) mechanism enables all users to share the 1Gbps bandwidth reasonably, guaranteeing a reliable QoS.
- ☑ Supports IGMP multicast, effective use of broadband;
- ☑ Supports multicast VLAN;
- ☑ Supports China Telecom CTC protocol;
- ☑ Full management through an Operation Administration Maintenance (OAM) protocol based on IEEE802.3ah, including configuration, alarm, performance monitoring, fault isolation and security management, etc. It supports remote management through OLT and local console management as well.
- ☑ Supports FEC and DBA;
- ☑ Supports IEEE802.1Q VLAN protocol;
- ☑ Supports IEEE 802.1p protocol;
- ☑ Supports remote loopback and network status diagnosis;
- ☑ Supports flow statistics;
- ☑ Supports storm control;

Technical Parameter

| Module | PU-E210 |
|-------------------|---|
| User interface | 1 10/100/1000M RJ45 port. |
| PON | Transmission speed :upstream/downstream symmetrical 1Gbps Network coverage radius: 20KM Optical receive sensitivity:≥-26dBm Luminous power: > 2dBm Security: ONU authentication mechanism |
| Protocol | Compliant with IEEE 802.3ah YD/T 1475-2006 IEEE 802.1D, Spanning Tree IEEE 802.1Q, VLAN IEEE 802.1w, RSTP IEEE 802.3ad (LACP) Ethernet-II, Ethernet-SNAP |
| VLAN | Port-based VLAN GVRP IEEE 802.1Q VLAN |
| QOS | Backpressure flow control(half-duplex) IEEE 802.3x flow control(full-duplex) Prevent Head Of Line IEEE 802.1p, CoS WR,SP and FIFO queue scheduling algorithm Port rate limit |
| Safety | IEEE 802.1x, access control based upon Port; support local and remote RADIUS. CHAP,EAP certification; Storm control, port protection, |
| Management | Various management modes such as CLI, Web, SNMP, TELNET and cluster Support remote reset and reboot SSHv1/v2 Software upgrade through TFTP and FTP. Network testing tools such as ping and traceroute |
| Size | 102mm(L) ×45mm(W) ×45mm(H) |
| Environment | Operating temperature:0℃~60℃; Operating humidity:10%~85% non-condensing |
| | Storage temperature:-40℃~80℃; Storage humidity:5%~95% non-condensing |
| Power supply | 110~240VAC 5V/1A DC power interface size:1.3mm/3.5mm |
| Power Consumption | 2.5W |